



ADHOC ARCOPRINT

range	size	grain	total substance	
	50x70	LG	182	381
	70x100	SG	182	272 381

face material High white Premium Quality uncoated paper and board, made with E.C.F. pulp. Exceptional look-through. Excellent formation and clarity.

technical features standard/instrument unit of measure	substance	thickness	brightness	opacity	tensile strength	
	ISO 536	ISO 536	ISO 2470	ISO 2471	ISO 1924	
	g/m ²	µm	%	%	KN/m	
					long	trasv
	80	100	110	88 ± 2	4,6	2,6
	170	210	110	98 ± 2	9,8	4,8
	300	375	110	-	14,4	6,5

adhesive Modified acrylic adhesives in water-based emulsion. Are available two types, permanent and removable. Both adhesives are approved for indirect food contacts and corresponding to UNI EN 71 “toy security” norms.

technical features unit of measure	tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
	g/25 mm	hours	°C	°C	°C
	SUPERTACK	1200	3	+ 5	- 10 + 80
	REMOVABLE	300	0,5	+ 5	- 10 + 80

backing materials Single glazed and monosilicone coated paper. Adhoc Arcoprint 381g version is only available with glassine protective in the version without crack-back.

technical features standard/instrument unit of measure	substance	thickness	opacity	tensile strength	
	ISO 536	ISO 536	ISO 2471	ISO 1924	
	g/m ²	µm	%	N/15 mm	
				long	trasv
	85	92	84	70	40
	63	56	-	80	40

notes Special runs for sizes and/or other adhesives available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.

Adhoc Arcoprint is a self-adhesive common used product.

[applications](#)

Can be used without problems with the main conventional printing systems; good results in the main cutting and die-cutting operations. The macro-porous surface suggests the use of oxidative drying inks. Good chromatic and tone performance, ink load, dot gain and printing contrast are at the highest level obtainable by uncoated papers. The self-adhesive product requires stable temperature and relative humidity conditions (20-22 °C and 50-55% U.R); for a good storage we suggest to pile the sheets (on pallet) at a maximum height of 1 meter and do not stack pallets. If it is necessary to cut the sheets for the printing, we suggest to use a very sharp guillotine blade with an angle next to 20°, cutting piles of a maximum height of 30 mm at a time, and using the lowest pressure possible in order to prevent adhesive bleed.

[general informations](#)

The shelf-life of a self-adhesive product is closely related, besides to storage conditions, to the nature of the adhesives and of the front materials used. At recommended storage conditions, the shelf-life with permanent adhesive is guaranteed for 18 months instead of removable adhesive that is guaranteed for one year.

[shelf life](#)



ADHOC FREELIFE VELLUM

range size grain total substance
50x70 LG 182

face material High quality paper with 40% recycled material certify FSC[®], 55% pure environmentally friendly fiber certify FSC[®] and 5% cotton fiber. Available in White shade.

technical features
standard/instrument
unit of measure

substance	thickness	brightness	opacity	tensile strength	
ISO 536	ISO 536	ISO 2470	ISO 2471	ISO 1924	
g/m ²	µm	%	%	Kg/15 mm	
				long	cross
80	104	87	89	5,2	2,4

adhesive Modified acrylic adhesive in water-based emulsion. Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect foodcontacts and corresponding to UNI EN 71 “toys security” norms.

technical features
unit of measure

tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
g/25 mm	hours	°C	°C	°C
SUPERTACK	1200	3	+ 5	- 10 + 80

backing material Single glazed and monosilicone coated white papers. Only available in box version, with or without crack-back.

technical features
standard/instrument
unit of measure

substance	thickness	opacity	tensile strength	
ISO 536	ISO 536	ISO 2471	ISO 1924	
g/m ²	µm	%	N/15 mm	
			long	cross
85	92	84	70	40

notes In the face material, given the considerable amount of recycled content within the product it is normal for there to be a slight variation in the shade and occasional small residues from the recycling process, from one making to the next. Special runs available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.

Adhoc Freelife Vellum is a common used self-adhesive product. Recommended for high quality labels, especially in the wine-making industry.

applications

Can be used without problems with the main conventional printing systems; good results in the main cutting and die-cutting operations. The macro-porous surface suggests the use of oxidative drying inks. The self-adhesive product requires stable temperature and relative humidity conditions (20-22 °C and 50-55% U.R); for a good storage we suggest to pile the sheets (on pallet) at a maximum height of 1 meter and do not stack pallets. If it is necessary to cut the sheets for the printing, we suggest to use a very sharp guillotine blade with an angle next to 20°, cutting piles of a maximum height of 3 cm at a time, and using the lowest pressure possible in order to prevent adhesive bleed.

**general
informations**

The shelf-life of a self-adhesive product is closely related, besides to storage conditions, to the nature of the adhesives and of the front materials used. At recommended storage conditions, the shelf-life is guaranteed for 18 months.

shelf life